

# R200 Universal vinyl adhesive

**RLA Polymers Pty Ltd** 

Chemwatch: **14-60200** Version No: **2.1.1.1** 

Safety Data Sheet according to WHS and ADG requirements

Chemwatch Hazard Alert Code: 2

Issue Date: **05/11/2018**Print Date: **08/11/2018**L.GHS.AUS.EN

## SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

#### **Product Identifier**

Product name	R200 Universal vinyl adhesive
Synonyms	R200
Other means of identification	Not Available

## Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Flooring adhesive.

## Details of the supplier of the safety data sheet

Registered company name	RLA Polymers Pty Ltd	
Address	215 Colchester Road Kilsyth VIC 3137 Australia	
Telephone	+61 3 9728 1644	
Fax	61 3 9728 6009	
Website	www.rlagroup.com.au	
Email	sales@rlagroup.com.au	

## Emergency telephone number

Association / Organisation	Not Available	
Emergency telephone numbers	61 3 9728 1644 (RLA Group Technical Manager) business hours	
Other emergency telephone numbers	132766 (Security Monitoring Service)	

## **SECTION 2 HAZARDS IDENTIFICATION**

## Classification of the substance or mixture

## HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

Poisons Schedule	Not Applicable	
Classification [1]	Skin Sensitizer Category 1	
Legend: 1. Classified by Chemwatch; 2. Classification drawn from HSIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI		

## Label elements

Hazard pictogram(s)



SIGNAL WORD WARNING

## Hazard statement(s)

H317 May cause an allergic skin reaction.

#### Precautionary statement(s) Prevention

1 Toodan on any state mental of the state of		
P280	Wear protective gloves/protective clothing/eye protection/face protection.	
P261	Avoid breathing mist/vapours/spray.	
P272	72 Contaminated work clothing should not be allowed out of the workplace.	

Chemwatch: 14-60200 Page 2 of 7 Issue Date: 05/11/2018 Version No: 2.1.1.1 Print Date: 08/11/2018

## R200 Universal vinyl adhesive

P363	Wash contaminated clothing before reuse.	
P302+P352	IF ON SKIN: Wash with plenty of soap and water.	
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.	

## Precautionary statement(s) Storage

Not Applicable

## Precautionary statement(s) Disposal

P501

Dispose of contents/container in accordance with local regulations.

## **SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS**

#### Substances

See section below for composition of Mixtures

#### Mixtures

CAS No	%[weight]	Name
8050-09-7	1-3	rosin-colophony
112-34-5	1-2	diethylene glycol monobutyl ether
	>60	Ingredients determined not to be hazardous

## **SECTION 4 FIRST AID MEASURES**

## Description of first aid measures

Eye Contact	If this product comes in contact with the eyes:  Wash out immediately with fresh running water.  Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.  Seek medical attention without delay; if pain persists or recurs seek medical attention.  Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.	
Skin Contact	If skin contact occurs:  ► Immediately remove all contaminated clothing, including footwear.  ► Flush skin and hair with running water (and soap if available).  ► Seek medical attention in event of irritation.	
Inhalation	<ul> <li>If fumes, aerosols or combustion products are inhaled remove from contaminated area.</li> <li>Other measures are usually unnecessary.</li> </ul>	
Ingestion	<ul> <li>If swallowed do NOT induce vomiting.</li> <li>If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>Observe the patient carefully.</li> <li>Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>Seek medical advice.</li> </ul>	

#### Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## **SECTION 5 FIREFIGHTING MEASURES**

#### **Extinguishing media**

- ▶ There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

### Special hazards arising from the substrate or mixture

·			
Fire Incompatibility	None known.		
Advice for firefighters			
Fire Fighting	<ul> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Wear breathing apparatus plus protective gloves in the event of a fire.</li> <li>Prevent, by any means available, spillage from entering drains or water courses.</li> <li>Use fire fighting procedures suitable for surrounding area.</li> </ul>		
Fire/Explosion Hazard    Not combustible.			
HAZCHEM	Not Applicable		

## **SECTION 6 ACCIDENTAL RELEASE MEASURES**

# Personal precautions, protective equipment and emergency procedures

See section 8

## **Environmental precautions**

Chemwatch: 14-60200 Page 3 of 7

#### R200 Universal vinyl adhesive

Issue Date: 05/11/2018 Print Date: 08/11/2018

See section 12

Version No: 2.1.1.1

#### Methods and material for containment and cleaning up

#### Minor Spills

- ► Clean up all spills immediately.
- · Avoid breathing vapours and contact with skin and eyes.
- Control personal contact with the substance, by using protective equipment.
- ▶ Contain and absorb spill with sand, earth, inert material or vermiculite

#### **Major Spills**

## Moderate hazard.

- ▶ Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## **SECTION 7 HANDLING AND STORAGE**

#### Precautions for safe handling

	<ul> <li>Avoid all p</li> </ul>
Safe handling	<ul><li>Wear prote</li></ul>
	▶ Use in a w
	<ul> <li>Avoid conf</li> </ul>
	▶ Store in o

- ▶ DO NOT allow clothing wet with material to stay in contact with skin
- personal contact, including inhalation
- tective clothing when risk of exposure occurs.
- well-ventilated area.
- ntact with moisture.
- Other information
- in original containers.
- ▶ Keep containers securely sealed.
- ► Store in a cool, dry, well-ventilated area.
- ▶ Store away from incompatible materials and foodstuff containers.

#### Conditions for safe storage, including any incompatibilities

Suitable container

- ▶ Polyethylene or polypropylene container.
- Packing as recommended by manufacturer.
- ► Check all containers are clearly labelled and free from leaks.

Storage incompatibility None known

#### **SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION**

## **Control parameters**

OCCUPATIONAL EXPOSURE LIMITS (OEL)

#### INGREDIENT DATA

Not Available

#### **EMERGENCY LIMITS**

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
rosin-colophony	Rosin core solder decomposition products; (Colophony Gum)	72 mg/m3	790 mg/m3	1,500 mg/m3
diethylene glycol monobutyl ether	Butoxyethoxy)ethanol, 2-(2-; (Diethylene glycol monobutyl ether)	30 ppm	33 ppm	200 ppm

Ingredient	Original IDLH	Revised IDLH
rosin-colophony	Not Available	Not Available
diethylene glycol monobutyl ether	Not Available	Not Available

#### MATERIAL DATA

#### **Exposure controls**

## Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

## Personal protection











- Eve and face protection
- Safety glasses with side shields
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.

#### Skin protection

#### See Hand protection below

- ▶ Wear chemical protective gloves, e.g. PVC. ▶ Wear safety footwear or safety gumboots, e.g. Rubber

#### Hands/feet protection

- NOTE: ▶ The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to
- avoid all possible skin contact. ▶ Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.

Chemwatch: 14-60200 Page 4 of 7 Issue Date: 05/11/2018 Version No: 2.1.1.1 Print Date: 08/11/2018

# R200 Universal vinyl adhesive

	The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.  The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.  Personal hygiene is a key element of effective hand care.
Body protection	See Other protection below
Other protection	► Overalls.  ► P.V.C. apron.  ► Barrier cream.

#### Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Required minimum protection factor	Maximum gas/vapour concentration present in air p.p.m. (by volume)	Half-face Respirator	Full-Face Respirator
up to 10	1000	A-AUS / Class1 P2	-
up to 50	1000	-	A-AUS / Class 1 P2
up to 50	5000	Airline *	-
up to 100	5000	-	A-2 P2
up to 100	10000	-	A-3 P2
100+			Airline**

<sup>\* -</sup> Continuous Flow \*\* - Continuous-flow or positive pressure demand

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

## **SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES**

## Information on basic physical and chemical properties

Appearance	Cream liquid; miscible with water.		
Physical state	Liquid	Relative density (Water = 1)	1.25
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	9.0	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	60,000 cps
Initial boiling point and boiling range (°C)	100	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

# **SECTION 10 STABILITY AND REACTIVITY**

Reactivity	See section 7
Chemical stability	<ul> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul>
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

## **SECTION 11 TOXICOLOGICAL INFORMATION**

Chemwatch: **14-60200** Page **5** of **7** Issue Date: **05/11/2018**Version No: **2.1.1.1** Print Date: **08/11/2018** 

#### R200 Universal vinyl adhesive

The material is not thought to produce either adverse health effects or irritation of the respiratory tract following inhalation (as classified by EC Directives Inhaled using animal models). Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. Ingestion Accidental ingestion of the material may be damaging to the health of the individual. Limited evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant inflammation when applied to the healthy intact skin of animals, for up to four hours, such inflammation being present twenty-four hours or more after the end of the exposure period. Skin irritation may also be present after prolonged or repeated exposure: this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may Skin Contact progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects, Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. Eve Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn) Practical experience shows that skin contact with the material is capable either of inducing a sensitisation reaction in a substantial number of individuals, and/or of producing a positive response in experimental animals. Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems. Chronic Rosin (colophany) has caused allergic contact dermatitis in solderers using resin flux-cored solders, can be a sensitiser for strings players, and has caused dermatitis after use in adhesive tapes [NIOSHTEC]. It is found in many products that commonly come in contact with the skin, including cosmetics, sunscreens, veterinary medications, adhesives, sealants, polishes, paints and oils, Industrial use of rosins (both natural and modified) is common and they are found in such products as printing inks, cutting fluids, corrosion inhibitors and surface coatings. High-quality gloss paper may also be coated with rosin or its derivatives. TOXICITY IRRITATION R200 Universal vinyl adhesive Not Available Not Available TOXICITY IRRITATION Not Available dermal (rat) LD50: >2-000 mg/kg<sup>[1]</sup> rosin-colophony Oral (rat) LD50: >1-000 mg/kg<sup>[1]</sup> TOXICITY IRRITATION diethylene glycol monobutyl Dermal (rabbit) LD50: >2000 mg/kg<sup>[2]</sup> Eye (rabbit): 20 mg/24h moderate ether Oral (rat) LD50: =4500 mg/kg<sup>[2]</sup> Eve (rabbit): 5 mg - SEVERE 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.\* Value obtained from manufacturer's SDS. Unless otherwise specified Legend: data extracted from RTECS - Register of Toxic Effect of chemical Substances The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema ROSIN-COLOPHONY involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce coniunctivitis For diethylene glycol monoalkyl ethers and their acetates: DIETHYLENE GLYCOL This category includes diethylene glycol ethyl ether (DGEE), diethylene glycol propyl ether (DGPE) diethylene glycol butyl ether (DGBE) and diethylene MONOBUTYL ETHER glycol hexyl ether (DGHE) and their acetates Acute toxicity: There are adequate oral, inhalation and/or dermal toxicity studies on the category members. Oral LD50 values in rats for all category members are all > 3000 mg/kg bw, with values generally decreasing with increasing molecular weight. Four to eight hour acute inhalation toxicity studies were conducted for all category members except DGPE in rats at the highest vapour concentrations achievable. **Acute Toxicity** 0 Carcinogenicity 0 Skin Irritation/Corrosion 0 Reproductivity Serious Eye Damage/Irritation 0 STOT - Single Exposure 0 Respiratory or Skin STOT - Repeated Exposure 0 sensitisation Mutagenicity 0 **Aspiration Hazard** 0

Legend:

X - Data available but does not fill the criteria for classification

✓ – Data available to make classification

O - Data Not Available to make classification

#### **SECTION 12 ECOLOGICAL INFORMATION**

#### Toxicity

	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
R200 Universal vinyl adhesive	Not Available	Not Available	Not Available	Not Available	Not Available

Chemwatch: 14-60200 Page 6 of 7 Issue Date: 05/11/2018 Version No: 2.1.1.1 Print Date: 08/11/2018

#### R200 Universal vinyl adhesive

rosin-colophony	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	0.144mg/L	3
	EC50	48	Crustacea	=4.5mg/L	1
	EC50	96	Algae or other aquatic plants	0.170mg/L	3
			ı		
diethylene glycol monobutyl ether	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	488.016mg/L	3
	EC50	48	Crustacea	>100mg/L	1
	EC50	96	Algae or other aquatic plants	>100mg/L	1
	NOEC	96	Algae or other aquatic plants	>=100mg/L	1

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

#### DO NOT discharge into sewer or waterways.

#### Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
rosin-colophony	HIGH	HIGH
diethylene glycol monobutyl ether	LOW	LOW

#### **Bioaccumulative potential**

Ingredient	Bioaccumulation	
rosin-colophony	HIGH (LogKOW = 6.4607)	
diethylene glycol monobutyl ether	LOW (BCF = 0.46)	

#### Mobility in soil

Ingredient	Mobility
rosin-colophony	LOW (KOC = 21990)
diethylene glycol monobutyl ether	LOW (KOC = 10)

## **SECTION 13 DISPOSAL CONSIDERATIONS**

## Waste treatment methods

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- ▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- ▶ Where in doubt contact the responsible authority.
- Product / Packaging disposal
- ▶ Recycle wherever possible.
- ▶ Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or incineration in a licensed apparatus (after admixture with suitable combustible material).
- ► Decontaminate empty containers.

## **SECTION 14 TRANSPORT INFORMATION**

#### Labels Required

Labels Required	Labels Required	
Marine Pollutant	NO	
	Not Applicable	
HAZCHEM	Not Applicable	

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

## **SECTION 15 REGULATORY INFORMATION**

Safety, health and environmental regulations / legislation specific for the substance or mixture

ROSIN-COLOPHONY(8050-09-7) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Chemwatch: **14-60200** Page **7** of **7** Issue Date: **05/11/2018** 

Version No: 2.1.1.1 R200 Universal vinyl adhesive Print Date: 08/11/2018

Australia Inventory of Chemical Substances (AICS)

## DIETHYLENE GLYCOL MONOBUTYL ETHER(112-34-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals
Australia Inventory of Chemical Substances (AICS)
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix
E (Part 2)

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix F (Part 3)

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5

#### **National Inventory Status**

National Inventory	Status	
Australia - AICS	N (Ingredients determined not to be hazardous) Non-disclosed ingredients	
Canada - DSL	N (Ingredients determined not to be hazardous) Non-disclosed ingredients	
Canada - NDSL	N (rosin-colophony; diethylene glycol monobutyl ether; Ingredients determined not to be hazardous) Non-disclosed ingredients	
China - IECSC	N (Ingredients determined not to be hazardous) Non-disclosed ingredients	
Europe - EINEC / ELINCS / NLP	N (Ingredients determined not to be hazardous) Non-disclosed ingredients	
Japan - ENCS	N (rosin-colophony; Ingredients determined not to be hazardous) Non-disclosed ingredients	
Korea - KECI	N (Ingredients determined not to be hazardous) Non-disclosed ingredients	
New Zealand - NZIoC	N (Ingredients determined not to be hazardous) Non-disclosed ingredients	
Philippines - PICCS	N (Ingredients determined not to be hazardous) Non-disclosed ingredients	
USA - TSCA	N (Ingredients determined not to be hazardous) Non-disclosed ingredients	
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)	

## **SECTION 16 OTHER INFORMATION**

Revision Date	05/11/2018
Initial Date	05/11/2018

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chernwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

## **Definitions and abbreviations**

PC-TWA: Permissible Concentration-Time Weighted Average

 ${\sf PC-STEL} : {\sf Permissible Concentration-Short Term Exposure Limit}$ 

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit $_{\circ}$ 

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.