

101S Skirting Contact Adhesive

Roberts 101S Skirting Contact Adhesive is a specifically formulated solvent based (flammable), rapid drying contact cement, which has high strength, excellent ageing and heat resistance.

Roberts 101S Skirting Contact Adhesive is designed for use on most types of vinyl and plastic skirtings, cover-strips, plastic and metal treads and nosings, etc.

Not recommended for exterior application.

SURFACE PREPARATION

Surface to be bonded must be clean, dry and free from oil, dust, loose paint and other foreign materials.

APPLICATION

Apply adhesive liberally with brush, roller or notched trowel. Both bonding surfaces must be coated evenly and allowed to dry until 'touch dry'. This will take a minimum of 5-10 minutes at 20°C. They should be joined within 45 minutes of application.

CLEAN UP

To clean up equipment and adhesive spills, use Roberts 900 Contact Cleaner (flammable).

Roberts 900 is not recommended for removing adhesive from carpet, vinyl or lacquered surfaces.

If the adhesive has thickened beyond the point of easy application, think to original consistency with Roberts 900.

SHELF LIFE

Up to 1 year in a sealed container at 20°C.

PACKAGING

20 litre, 4 litre & 1 litre units.

COVERAGE

Up to 5m² per litre bonding surface.

The application, use and processing of our products is the responsibility of the user. Any technical or other advice, information or data provided by us, whether verbally, in writing or by way of trials or tests, is given without guarantee or warranty. Refer to Material Safety Data Sheets for information on Storage & Handling, Health and Safety, and Transport.

RLA POLYMERS PTY LTD

ACN 004 709 915

215 Colchester Road, Kilsyth, Victoria 3137 Australia

P.O. Box 147, Kilsyth, Victoria 3137 Australia

Telephone: (03) 9728 1644 • Facsimile: (03) 9728 6009

E-mail: info@rlapolymers.com.au • Web: www.rlapolymers.com.au



67 Dalgety Drive (P.O. Box 97-575)
Manukau City, Auckland, New Zealand

Telephone: (9) 268 0301

Facsimile: (9) 268 0305

RLA 044B

TYPICAL PROPERTIES

Appearance	Pale yellow
Base	Neoprene Synthetic Rubber
Solids	Approx. 22%
Viscosity	Thin syrup
Flash Point	Less than 0°C



CONTAINS

650 ml/litre liquid hydrocarbons
250 ml/litre ketones

HIGHLY FLAMMABLE

Avoid contact with skin and eyes and avoid breathing vapour or spray mist.

FIRST AID

If poisoning occurs, contact a doctor or Poisons Information Centre.

If swallowed, **DO NOT** induce vomiting. Give a glass of water.

SAFETY DIRECTIONS

Storage

Storage and use of this product is controlled by local, state and Commonwealth Government regulations.

Store in a well ventilated area away from oxidising agents.

In use, please ensure that Occupational Health and Safety requirements are observed. Work areas should be well ventilated and free of ignition sources. Prolonged skin contact or inhalation of vapours is advised against.

SAFETY AND HANDLING

Material Safety Data Sheet is available upon request.

Issued: March 2010

adhesives hot melt tapes
levelling powders