

R101S

RLA Polymers Pty Ltd

Chemwatch: 14-45670

Version No: 2.1.1.1

Safety Data Sheet according to WHS and ADG requirements

Chemwatch Hazard Alert Code: 3

Issue Date: 23/10/2018

Print Date: 25/10/2018

S.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

| | |
|-------------------------------|---------------------------------------|
| Product name | R101S |
| Synonyms | Not Available |
| Proper shipping name | ADHESIVES containing flammable liquid |
| Other means of identification | Not Available |

Relevant identified uses of the substance or mixture and uses advised against

| | |
|--------------------------|---|
| Relevant identified uses | The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing. Before starting consider control of exposure by mechanical ventilation. Brushable solvent based contact adhesive. |
|--------------------------|---|

Details of the supplier of the safety data sheet

| | |
|-------------------------|--|
| Registered company name | RLA Polymers Pty Ltd |
| Address | 215 Colchester Road Kilsyth VIC 3137 Australia |
| Telephone | +61 3 9728 1644 |
| Fax | +61 3 9728 6009 |
| Website | www.rlagroup.com.au |
| Email | sales@rlagroup.com.au |

Emergency telephone number

| | |
|-----------------------------------|--|
| Association / Organisation | Not Available |
| Emergency telephone numbers | +61 3 9728 1644 (RLA Group Technical Manager) business hours |
| Other emergency telephone numbers | 132766 (Security Monitoring Service) |

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

| | |
|-------------------------------|--|
| Poisons Schedule | S5 |
| Classification ^[1] | Flammable Liquid Category 2, Acute Toxicity (Oral) Category 4, Skin Corrosion/Irritation Category 2, Eye Irritation Category 2A, Reproductive Toxicity Category 2, Specific target organ toxicity - single exposure Category 3 (respiratory tract irritation), Specific target organ toxicity - single exposure Category 3 (narcotic effects), Specific target organ toxicity - repeated exposure Category 2, Aspiration Hazard Category 1 |
| Legend: | 1. Classified by Chemwatch; 2. Classification drawn from HSIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI |

Label elements

| | |
|---------------------|---|
| Hazard pictogram(s) |  |
| SIGNAL WORD | DANGER |

Hazard statement(s)

| | |
|------|--|
| H225 | Highly flammable liquid and vapour. |
| H302 | Harmful if swallowed. |
| H315 | Causes skin irritation. |
| H319 | Causes serious eye irritation. |
| H361 | Suspected of damaging fertility or the unborn child. |
| H335 | May cause respiratory irritation. |

| | |
|--------|--|
| H336 | May cause drowsiness or dizziness. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H304 | May be fatal if swallowed and enters airways. |
| AUH066 | Repeated exposure may cause skin dryness and cracking. |

Precautionary statement(s) Prevention

| | |
|------|--|
| P201 | Obtain special instructions before use. |
| P210 | Keep away from heat/sparks/open flames/hot surfaces. - No smoking. |
| P260 | Do not breathe dust/fume/gas/mist/vapours/spray. |
| P271 | Use in a well-ventilated area. |

Precautionary statement(s) Response

| | |
|-----------|---|
| P301+P310 | IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. |
| P308+P313 | IF exposed or concerned: Get medical advice/attention. |
| P331 | Do NOT induce vomiting. |
| P362 | Take off contaminated clothing and wash before reuse. |

Precautionary statement(s) Storage

| | |
|-----------|--|
| P403+P235 | Store in a well-ventilated place. Keep cool. |
| P405 | Store locked up. |

Precautionary statement(s) Disposal

| | |
|------|---|
| P501 | Dispose of contents/container in accordance with local regulations. |
|------|---|

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS**Substances**

See section below for composition of Mixtures

Mixtures

| CAS No | %[weight] | Name |
|----------|-----------|----------------------------|
| 108-88-3 | 10-30 | <u>toluene</u> |
| 78-93-3 | 10-30 | <u>methyl ethyl ketone</u> |
| 107-83-5 | 30-60 | <u>2-methylpentane</u> |

SECTION 4 FIRST AID MEASURES**Description of first aid measures**

| | |
|---------------------|--|
| Eye Contact | <p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> ▶ Wash out immediately with fresh running water. ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▶ Seek medical attention without delay; if pain persists or recurs seek medical attention. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. |
| Skin Contact | <p>If skin contact occurs:</p> <ul style="list-style-type: none"> ▶ Immediately remove all contaminated clothing, including footwear. ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation. |
| Inhalation | <ul style="list-style-type: none"> ▶ If fumes or combustion products are inhaled remove from contaminated area. ▶ Lay patient down. Keep warm and rested. ▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. ▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. ▶ Transport to hospital, or doctor, without delay. |
| Ingestion | <ul style="list-style-type: none"> ▶ If swallowed do NOT induce vomiting. ▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. ▶ Observe the patient carefully. ▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. ▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. ▶ Seek medical advice. ▶ Avoid giving milk or oils. ▶ Avoid giving alcohol. ▶ If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus. |

Indication of any immediate medical attention and special treatment needed

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it is considered necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours.

for simple ketones:

BASIC TREATMENT

Continued...

- ▶ Establish a patent airway with suction where necessary.
- ▶ Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- ▶ Administer oxygen by non-rebreather mask at 10 to 15 l/min.
- ▶ Monitor and treat, where necessary, for pulmonary oedema .
- ▶ Monitor and treat, where necessary, for shock.
- ▶ **DO NOT use emetics.** Where ingestion is suspected rinse mouth and give up to 200 ml water (5mL/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.
- ▶ Give activated charcoal.

ADVANCED TREATMENT

- ▶ Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- ▶ Consider intubation at first sign of upper airway obstruction resulting from oedema.
- ▶ Positive-pressure ventilation using a bag-valve mask might be of use.
- ▶ Monitor and treat, where necessary, for arrhythmias.
- ▶ Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- ▶ Drug therapy should be considered for pulmonary oedema.
- ▶ Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- ▶ Treat seizures with diazepam.
- ▶ Proparacaine hydrochloride should be used to assist eye irrigation.

EMERGENCY DEPARTMENT

- ▶ Laboratory analysis of complete blood count, serum electrolytes, BUN, creatinine, glucose, urinalysis, baseline for serum aminotransferases (ALT and AST), calcium, phosphorus and magnesium, may assist in establishing a treatment regime. Other useful analyses include anion and osmolar gaps, arterial blood gases (ABGs), chest radiographs and electrocardiograph.
- ▶ Positive end-expiratory pressure (PEEP)-assisted ventilation may be required for acute parenchymal injury or adult respiratory distress syndrome.
- ▶ Consult a toxicologist as necessary.

BRONSTEIN, A.C. and CURRANCE, P.L.

EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

Following acute or short term repeated exposures to toluene:

- ▶ Toluene is absorbed across the alveolar barrier, the blood/air mixture being 11.2/15.6 (at 37 degrees C.) The concentration of toluene, in expired breath, is of the order of 18 ppm following sustained exposure to 100 ppm. The tissue/blood proportion is 1/3 except in adipose where the proportion is 8/10.
- ▶ Metabolism by microsomal mono-oxygenation, results in the production of hippuric acid. This may be detected in the urine in amounts between 0.5 and 2.5 g/24 hr which represents, on average 0.8 gm/gm of creatinine. The biological half-life of hippuric acid is in the order of 1-2 hours.
- ▶ Primary threat to life from ingestion and/or inhalation is respiratory failure.
- ▶ Patients should be quickly evaluated for signs of respiratory distress (eg cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO₂ <50 mm Hg or pCO₂ > 50 mm Hg) should be intubated.
- ▶ Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial damage has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.
- ▶ A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.
- ▶ Epinephrine (adrenaline) is not recommended for treatment of bronchospasm because of potential myocardial sensitisation to catecholamines. Inhaled cardioselective bronchodilators (e.g. Alupent, Salbutamol) are the preferred agents, with aminophylline a second choice.
- ▶ Lavage is indicated in patients who require decontamination; ensure use.

BIOLOGICAL EXPOSURE INDEX - BEI

These represent the determinants observed in specimens collected from a healthy worker exposed at the Exposure Standard (ES or TLV):

| Determinant | Index | Sampling Time | Comments |
|------------------------|--------------------|---------------------------------|----------|
| o-Cresol in urine | 0.5 mg/L | End of shift | B |
| Hippuric acid in urine | 1.6 g/g creatinine | End of shift | B, NS |
| Toluene in blood | 0.05 mg/L | Prior to last shift of workweek | |

NS: Non-specific determinant; also observed after exposure to other material

B: Background levels occur in specimens collected from subjects NOT exposed

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

- ▶ Alcohol stable foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- ▶ Carbon dioxide.

Special hazards arising from the substrate or mixture

| | |
|-----------------------------|--|
| Fire Incompatibility | ▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result |
|-----------------------------|--|

Advice for firefighters

| | |
|------------------------------|---|
| Fire Fighting | <ul style="list-style-type: none"> ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ May be violently or explosively reactive. ▶ Wear breathing apparatus plus protective gloves in the event of a fire. ▶ Prevent, by any means available, spillage from entering drains or water course. |
| Fire/Explosion Hazard | <ul style="list-style-type: none"> ▶ Liquid and vapour are highly flammable. ▶ Severe fire hazard when exposed to heat, flame and/or oxidisers. ▶ Vapour may travel a considerable distance to source of ignition. ▶ Heating may cause expansion or decomposition leading to violent rupture of containers. <p>Combustion products include: carbon dioxide (CO₂) other pyrolysis products typical of burning organic material.</p> <p>Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions. May emit clouds of acrid smoke</p> |
| HAZCHEM | *3YE |

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

| | |
|---------------------|--|
| Minor Spills | <ul style="list-style-type: none"> ▶ Remove all ignition sources. ▶ Clean up all spills immediately. ▶ Avoid breathing vapours and contact with skin and eyes. ▶ Control personal contact with the substance, by using protective equipment. |
| Major Spills | <ul style="list-style-type: none"> ▶ Clear area of personnel and move upwind. ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ May be violently or explosively reactive. ▶ Wear breathing apparatus plus protective gloves. |

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

| | |
|--------------------------|---|
| Safe handling | <p>The conductivity of this material may make it a static accumulator. A liquid is typically considered nonconductive if its conductivity is below 100 pS/m and is considered semi-conductive if its conductivity is below 10 000 pS/m. Whether a liquid is nonconductive or semi-conductive, the precautions are the same. A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid.</p> <ul style="list-style-type: none"> ▶ Containers, even those that have been emptied, may contain explosive vapours. ▶ Do NOT cut, drill, grind, weld or perform similar operations on or near containers. <p>Contains low boiling substance: Storage in sealed containers may result in pressure buildup causing violent rupture of containers not rated appropriately.</p> <ul style="list-style-type: none"> ▶ Check for bulging containers. ▶ Vent periodically ▶ Always release caps or seals slowly to ensure slow dissipation of vapours ▶ DO NOT allow clothing wet with material to stay in contact with skin ▶ Electrostatic discharge may be generated during pumping - this may result in fire. ▶ Ensure electrical continuity by bonding and grounding (earthing) all equipment. ▶ Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (≤ 1 m/sec until fill pipe submerged to twice its diameter, then ≤ 7 m/sec). ▶ Avoid splash filling. ▶ Avoid all personal contact, including inhalation. ▶ Wear protective clothing when risk of exposure occurs. ▶ Use in a well-ventilated area. ▶ Prevent concentration in hollows and sumps. |
| Other information | <ul style="list-style-type: none"> ▶ Store in original containers in approved flame-proof area. ▶ No smoking, naked lights, heat or ignition sources. ▶ DO NOT store in pits, depressions, basements or areas where vapours may be trapped. ▶ Keep containers securely sealed. |

Conditions for safe storage, including any incompatibilities

| | |
|--------------------------------|--|
| Suitable container | <ul style="list-style-type: none"> ▶ Packing as supplied by manufacturer. ▶ Plastic containers may only be used if approved for flammable liquid. ▶ Check that containers are clearly labelled and free from leaks. ▶ For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure. ▶ For materials with a viscosity of at least 2680 cSt. (23 deg. C) ▶ For manufactured product having a viscosity of at least 250 cSt. |
| Storage incompatibility | <p>For alkyl aromatics:</p> <p>The alkyl side chain of aromatic rings can undergo oxidation by several mechanisms. The most common and dominant one is the attack by oxidation at benzylic carbon as the intermediate formed is stabilised by resonance structure of the ring.</p> <ul style="list-style-type: none"> ▶ Following reaction with oxygen and under the influence of sunlight, a hydroperoxide at the alpha-position to the aromatic ring, is the primary oxidation product formed (provided a hydrogen atom is initially available at this position) - this product is often short-lived but may be stable dependent on the nature of the aromatic substitution; a secondary C-H bond is more easily attacked than a primary C-H bond whilst a tertiary C-H bond is even more susceptible to attack by oxygen ▶ Monoalkylbenzenes may subsequently form monocarboxylic acids; alkyl naphthalenes mainly produce the corresponding naphthalene carboxylic acids. ▶ Oxidation in the presence of transition metal salts not only accelerates but also selectively decomposes the hydroperoxides. ▶ Vigorous reactions, sometimes amounting to explosions, can result from the contact between aromatic rings and strong oxidising agents. ▶ Aromatics can react exothermically with bases and with diazo compounds. |

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

| Source | Ingredient | Material name | TWA | STEL | Peak | Notes |
|------------------------------|------------|---------------|--------------------------------|---------------------------------|---------------|---------------|
| Australia Exposure Standards | toluene | Toluene | 50 ppm / 191 mg/m ³ | 574 mg/m ³ / 150 ppm | Not Available | Not Available |


| | | | | | | |
|------------------------------|---------------------|---------------------------|----------------------|-----------------------|---------------|---------------|
| Australia Exposure Standards | methyl ethyl ketone | Methyl ethyl ketone (MEK) | 150 ppm / 445 mg/m3 | 890 mg/m3 / 300 ppm | Not Available | Not Available |
| Australia Exposure Standards | 2-methylpentane | Hexane, other isomers | 500 ppm / 1760 mg/m3 | 3500 mg/m3 / 1000 ppm | Not Available | Not Available |

EMERGENCY LIMITS

| Ingredient | Material name | TEEL-1 | TEEL-2 | TEEL-3 |
|---------------------|--|---------------|---------------|---------------|
| toluene | Toluene | Not Available | Not Available | Not Available |
| methyl ethyl ketone | Butanone, 2-; (Methyl ethyl ketone; MEK) | Not Available | Not Available | Not Available |
| 2-methylpentane | Methylpentane, 2-; (Isohexane) | 1,000 ppm | 11000 ppm | 66000 ppm |

| Ingredient | Original IDLH | Revised IDLH |
|---------------------|---------------|---------------|
| toluene | 500 ppm | Not Available |
| methyl ethyl ketone | 3,000 ppm | Not Available |
| 2-methylpentane | Not Available | Not Available |

Exposure controls

| | |
|---|---|
| Appropriate engineering controls | <p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.</p> <p>The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.</p> |
| Personal protection |  |
| Eye and face protection | <ul style="list-style-type: none"> ▶ Safety glasses with side shields. ▶ Chemical goggles. ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. |
| Skin protection | See Hand protection below |
| Hands/feet protection | <ul style="list-style-type: none"> ▶ Wear chemical protective gloves, e.g. PVC. ▶ Wear safety footwear or safety gumboots, e.g. Rubber <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</p> <p>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</p> <p>Personal hygiene is a key element of effective hand care.</p> |
| Body protection | See Other protection below |
| Other protection | <ul style="list-style-type: none"> ▶ Overalls. ▶ PVC Apron. ▶ PVC protective suit may be required if exposure severe. ▶ Eyewash unit. ▶ Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity. ▶ For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets). ▶ Non sparking safety or conductive footwear should be considered. Conductive footwear describes a boot or shoe with a sole made from a conductive compound chemically bound to the bottom components, for permanent control to electrically ground the foot and shall dissipate static electricity from the body to reduce the possibility of ignition of volatile compounds. |

Recommended material(s)**GLOVE SELECTION INDEX**

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:

R101S

| Material | CPI |
|------------------|-----|
| PE/EVAL/PE | A |
| PVA | B |
| TEFLON | B |
| BUTYL | C |
| BUTYL/NEOPRENE | C |
| CPE | C |
| HYPALON | C |
| NATURAL RUBBER | C |
| NATURAL+NEOPRENE | C |
| NEOPRENE | C |
| NEOPRENE/NATURAL | C |
| NITRILE | C |

Respiratory protection

Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

| Required Minimum Protection Factor | Half-Face Respirator | Full-Face Respirator | Powered Air Respirator |
|------------------------------------|----------------------|----------------------|------------------------|
| up to 5 x ES | AX-AUS / Class 1 | - | AX-PAPR-AUS / Class 1 |
| up to 25 x ES | Air-line* | AX-2 | AX-PAPR-2 |
| up to 50 x ES | - | AX-3 | - |
| 50+ x ES | - | Air-line** | - |

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO₂), G = Agricultural chemicals, K = Ammonia(NH₃), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on

| | |
|-------------------|---|
| NITRILE+PVC | C |
| PVC | C |
| SARANEX-23 | C |
| SARANEX-23 2-PLY | C |
| VITON | C |
| VITON/CHLOROBUTYL | C |
| VITON/NEOPRENE | C |

detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.

Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

| | | | |
|---|---|--|----------------|
| Appearance | Thin yellow liquid with hydrocarbon odour; not miscible with water. | | |
| Physical state | Liquid | Relative density (Water = 1) | 0.82 |
| Odour | Not Available | Partition coefficient n-octanol / water | Not Available |
| Odour threshold | Not Available | Auto-ignition temperature (°C) | Not Available |
| pH (as supplied) | Not Applicable | Decomposition temperature | Not Available |
| Melting point / freezing point (°C) | Not Available | Viscosity (cSt) | Not Available |
| Initial boiling point and boiling range (°C) | 55-111 | Molecular weight (g/mol) | Not Applicable |
| Flash point (°C) | -29 (2-methylpentane) | Taste | Not Available |
| Evaporation rate | Not Available | Explosive properties | Not Available |
| Flammability | HIGHLY FLAMMABLE. | Oxidising properties | Not Available |
| Upper Explosive Limit (%) | 7.1 | Surface Tension (dyn/cm or mN/m) | Not Available |
| Lower Explosive Limit (%) | 1.2 | Volatile Component (%vol) | Not Available |
| Vapour pressure (kPa) | 28 | Gas group | Not Available |
| Solubility in water (g/L) | Immiscible | pH as a solution (1%) | Not Available |
| Vapour density (Air = 1) | Not Available | VOC g/L | Not Available |

SECTION 10 STABILITY AND REACTIVITY

| | |
|---|--|
| Reactivity | See section 7 |
| Chemical stability | <ul style="list-style-type: none"> ▶ Unstable in the presence of incompatible materials. ▶ Product is considered stable. ▶ Hazardous polymerisation will not occur. |
| Possibility of hazardous reactions | See section 7 |
| Conditions to avoid | See section 7 |
| Incompatible materials | See section 7 |
| Hazardous decomposition products | See section 5 |

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

| | |
|----------------|---|
| Inhaled | <p>The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.</p> <p>Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination.</p> <p>Central nervous system (CNS) depression may include general discomfort, symptoms of giddiness, headache, dizziness, nausea, anaesthetic effects, slowed reaction time, slurred speech and may progress to unconsciousness. Serious poisonings may result in respiratory depression and may be fatal.</p> <p>Material is highly volatile and may quickly form a concentrated atmosphere in confined or unventilated areas. The vapour may displace and replace air in breathing zone, acting as a simple asphyxiant. This may happen with little warning of overexposure.</p> <p>Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual. Ketone vapours irritate the nose, throat and mucous membrane. High concentrations depress the central nervous system, causing headache, vertigo, poor concentration, sleep and failure of the heart and breathing.</p> |
|----------------|---|

| | |
|---------------------|---|
| Ingestion | Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual. Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733) Considered an unlikely route of entry in commercial/industrial environments. The liquid may produce gastrointestinal discomfort and may be harmful if swallowed. |
| Skin Contact | The material may cause moderate inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering. Repeated exposure may cause skin cracking, flaking or drying following normal handling and use. Skin contact with the material may damage the health of the individual; systemic effects may result following absorption. Open cuts, abraded or irritated skin should not be exposed to this material The material may accentuate any pre-existing dermatitis condition Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. |
| Eye | There is evidence that material may produce eye irritation in some persons and produce eye damage 24 hours or more after instillation. Severe inflammation may be expected with pain. |
| Chronic | Long-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related whole-body problems. This material can cause serious damage if one is exposed to it for long periods. It can be assumed that it contains a substance which can produce severe defects. Based on experience with animal studies, exposure to the material may result in toxic effects to the development of the foetus, at levels which do not cause significant toxic effects to the mother. Prolonged or repeated skin contact may cause drying with cracking, irritation and possible dermatitis following. There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment. Intentional abuse (glue sniffing) or occupational exposure to toluene can result in chronic habituation. Chronic abuse has caused inco-ordination, tremors of the extremities (due to widespread cerebrum withering), headache, abnormal speech, temporary memory loss, convulsions, coma, drowsiness, reduced colour perception, blindness, nystagmus (rapid, involuntary eye movements), hearing loss leading to deafness and mild dementia. Animal testing shows that methyl ethyl ketone may have slight effects on the nervous system, liver, kidney and respiratory system; there may also be developmental effects and an increase in birth defects. However, there is limited information available on the long-term effects of methyl ethyl ketone in humans, and no information is available on whether it causes developmental or reproductive toxicity or cancer. It is generally considered to have low toxicity, but it is often used in combination with other solvents, and the toxic effects of the mixture may be greater than with either solvent alone. Combinations of n-hexane or methyl n-butyl ketone with methyl ethyl ketone may increase the rate of peripheral neuropathy, a progressive disorder of the nerves of the extremities. Harmful: danger of serious damage to health by prolonged exposure through inhalation. |

| | | |
|----------------------------|---|------------------------------------|
| R101S | TOXICITY | IRRITATION |
| | Not Available | Not Available |
| toluene | TOXICITY | IRRITATION |
| | dermal (rat) LD50: =12124 mg/kg ^[2] | Eye (rabbit): 2mg/24h - SEVERE |
| | Inhalation (rat) LC50: 49 mg/l/4H ^[2] | Eye (rabbit):0.87 mg - mild |
| | Oral (rat) LD50: 636 mg/kg ^[2] | Eye (rabbit):100 mg/30sec - mild |
| | | Skin (rabbit):20 mg/24h-moderate |
| | | Skin (rabbit):500 mg - moderate |
| methyl ethyl ketone | TOXICITY | IRRITATION |
| | Dermal (rabbit) LD50: ~6400-8000 mg/kg ^[2] | Eye (human): 350 ppm -irritant |
| | Inhalation (rat) LC50: 47 mg/l/8H ^[2] | Eye (rabbit): 80 mg - irritant |
| | Oral (rat) LD50: 2054 mg/kg ^[1] | Skin (rabbit): 402 mg/24 hr - mild |
| | | Skin (rabbit):13.78mg/24 hr open |
| 2-methylpentane | TOXICITY | IRRITATION |
| | Not Available | Not Available |

Legend: 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. * Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

| | |
|--|---|
| TOLUENE | For toluene: Acute toxicity: Humans exposed to high levels of toluene for short periods of time experience adverse central nervous system effects ranging from headaches to intoxication, convulsions, narcosis (sleepiness) and death. When inhaled or swallowed, toluene can cause severe central nervous system depression, and in large doses has a narcotic effect. 60mL has caused death. Death of heart muscle fibres, liver swelling, congestion and bleeding of the lungs and kidney injury were all found on autopsy. |
| METHYL ETHYL KETONE | Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. Methyl ethyl ketone is considered to have a low order of toxicity; however, methyl ethyl ketone is often used in combination with other solvents and the mixture may have greater toxicity than either solvent alone. Combinations of n-hexane with methyl ethyl ketone, and also methyl n-butyl ketone with methyl ethyl ketone may result in an increased in peripheral neuropathy, a progressive disorder of the nerves of the extremities. Combinations with chloroform also show an increase in toxicity. |
| 2-METHYLPENTANE | No significant acute toxicological data identified in literature search. |
| TOLUENE & METHYL ETHYL KETONE | The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. |

R101S

| | | | |
|-----------------------------------|---|--------------------------|---|
| Acute Toxicity | ✓ | Carcinogenicity | ⊘ |
| Skin Irritation/Corrosion | ✓ | Reproductivity | ✓ |
| Serious Eye Damage/Irritation | ✓ | STOT - Single Exposure | ✓ |
| Respiratory or Skin sensitisation | ⊘ | STOT - Repeated Exposure | ✓ |
| Mutagenicity | ⊘ | Aspiration Hazard | ✓ |

Legend: ✗ – Data available but does not fill the criteria for classification

✓ – Data available to make classification

⊘ – Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

| R101S | ENDPOINT | TEST DURATION (HR) | SPECIES | VALUE | SOURCE |
|-------|---------------|--------------------|---------------|---------------|---------------|
| | Not Available | Not Available | Not Available | Not Available | Not Available |

| toluene | ENDPOINT | TEST DURATION (HR) | SPECIES | VALUE | SOURCE |
|---------|----------|--------------------|-------------------------------|------------|--------|
| | LC50 | 96 | Fish | 0.0073mg/L | 4 |
| | EC50 | 48 | Crustacea | 3.78mg/L | 5 |
| | EC50 | 72 | Algae or other aquatic plants | 12.5mg/L | 4 |
| | BCF | 24 | Algae or other aquatic plants | 10mg/L | 4 |
| | NOEC | 168 | Crustacea | 0.74mg/L | 5 |

| methyl ethyl ketone | ENDPOINT | TEST DURATION (HR) | SPECIES | VALUE | SOURCE |
|---------------------|----------|--------------------|-------------------------------|-----------|--------|
| | LC50 | 96 | Fish | 2-993mg/L | 2 |
| | EC50 | 48 | Crustacea | 308mg/L | 2 |
| | EC50 | 72 | Algae or other aquatic plants | 1-972mg/L | 2 |
| | NOEC | 96 | Fish | 1-170mg/L | 2 |

| 2-methylpentane | ENDPOINT | TEST DURATION (HR) | SPECIES | VALUE | SOURCE |
|-----------------|----------|--------------------|-------------------------------|-----------|--------|
| | LC50 | 96 | Fish | 1.915mg/L | 3 |
| | EC50 | 96 | Algae or other aquatic plants | 3.635mg/L | 3 |

Legend: Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

DO NOT discharge into sewer or waterways.

Persistence and degradability

| Ingredient | Persistence: Water/Soil | Persistence: Air |
|---------------------|---------------------------|------------------------------|
| toluene | LOW (Half-life = 28 days) | LOW (Half-life = 4.33 days) |
| methyl ethyl ketone | LOW (Half-life = 14 days) | LOW (Half-life = 26.75 days) |
| 2-methylpentane | LOW | LOW |

Bioaccumulative potential

| Ingredient | Bioaccumulation |
|---------------------|-----------------------|
| toluene | LOW (BCF = 90) |
| methyl ethyl ketone | LOW (LogKOW = 0.29) |
| 2-methylpentane | LOW (LogKOW = 3.2145) |

Mobility in soil

| Ingredient | Mobility |
|---------------------|----------------------|
| toluene | LOW (KOC = 268) |
| methyl ethyl ketone | MEDIUM (KOC = 3.827) |
| 2-methylpentane | LOW (KOC = 124.9) |



SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

| | |
|------------------------------|--|
| Product / Packaging disposal | <ul style="list-style-type: none"> ▶ Containers may still present a chemical hazard/ danger when empty. ▶ Return to supplier for reuse/ recycling if possible. <p>Otherwise:</p> <ul style="list-style-type: none"> ▶ If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill. ▶ Where possible retain label warnings and SDS and observe all notices pertaining to the product. <p>Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.</p> <p>A Hierarchy of Controls seems to be common - the user should investigate:</p> <ul style="list-style-type: none"> ▶ Reduction ▶ Reuse ▶ Recycling ▶ Disposal (if all else fails) <p>This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use.</p> <ul style="list-style-type: none"> ▶ DO NOT allow wash water from cleaning or process equipment to enter drains. ▶ It may be necessary to collect all wash water for treatment before disposal. ▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. ▶ Where in doubt contact the responsible authority. ▶ Recycle wherever possible. ▶ Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified. ▶ Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material). ▶ Decontaminate empty containers. |
|------------------------------|--|

SECTION 14 TRANSPORT INFORMATION

Labels Required

| | |
|------------------|---|
| |  |
| Marine Pollutant |  |
| HAZCHEM | *3YE |

Land transport (ADG)

| | | | | | |
|------------------------------|--|--------------------|----------------|------------------|----------------|
| UN number | 1133 | | | | |
| UN proper shipping name | ADHESIVES containing flammable liquid | | | | |
| Transport hazard class(es) | <table border="0"> <tr> <td>Class</td> <td>3</td> </tr> <tr> <td>Subrisk</td> <td>Not Applicable</td> </tr> </table> | Class | 3 | Subrisk | Not Applicable |
| Class | 3 | | | | |
| Subrisk | Not Applicable | | | | |
| Packing group | II | | | | |
| Environmental hazard | Environmentally hazardous | | | | |
| Special precautions for user | <table border="0"> <tr> <td>Special provisions</td> <td>Not Applicable</td> </tr> <tr> <td>Limited quantity</td> <td>5 L</td> </tr> </table> | Special provisions | Not Applicable | Limited quantity | 5 L |
| Special provisions | Not Applicable | | | | |
| Limited quantity | 5 L | | | | |

Air transport (ICAO-IATA / DGR)

| | | | | | | | | | | | | | | | |
|---|---|--------------------|----|---------------------------------|----------------|-------------------------------|------|--|-----|--|-----|---|------|--|-----|
| UN number | 1133 | | | | | | | | | | | | | | |
| UN proper shipping name | Adhesives containing flammable liquid | | | | | | | | | | | | | | |
| Transport hazard class(es) | <table border="0"> <tr> <td>ICAO/IATA Class</td> <td>3</td> </tr> <tr> <td>ICAO / IATA Subrisk</td> <td>Not Applicable</td> </tr> <tr> <td>ERG Code</td> <td>3L</td> </tr> </table> | ICAO/IATA Class | 3 | ICAO / IATA Subrisk | Not Applicable | ERG Code | 3L | | | | | | | | |
| ICAO/IATA Class | 3 | | | | | | | | | | | | | | |
| ICAO / IATA Subrisk | Not Applicable | | | | | | | | | | | | | | |
| ERG Code | 3L | | | | | | | | | | | | | | |
| Packing group | II | | | | | | | | | | | | | | |
| Environmental hazard | Environmentally hazardous | | | | | | | | | | | | | | |
| Special precautions for user | <table border="0"> <tr> <td>Special provisions</td> <td>A3</td> </tr> <tr> <td>Cargo Only Packing Instructions</td> <td>364</td> </tr> <tr> <td>Cargo Only Maximum Qty / Pack</td> <td>60 L</td> </tr> <tr> <td>Passenger and Cargo Packing Instructions</td> <td>353</td> </tr> <tr> <td>Passenger and Cargo Maximum Qty / Pack</td> <td>5 L</td> </tr> <tr> <td>Passenger and Cargo Limited Quantity Packing Instructions</td> <td>Y341</td> </tr> <tr> <td>Passenger and Cargo Limited Maximum Qty / Pack</td> <td>1 L</td> </tr> </table> | Special provisions | A3 | Cargo Only Packing Instructions | 364 | Cargo Only Maximum Qty / Pack | 60 L | Passenger and Cargo Packing Instructions | 353 | Passenger and Cargo Maximum Qty / Pack | 5 L | Passenger and Cargo Limited Quantity Packing Instructions | Y341 | Passenger and Cargo Limited Maximum Qty / Pack | 1 L |
| Special provisions | A3 | | | | | | | | | | | | | | |
| Cargo Only Packing Instructions | 364 | | | | | | | | | | | | | | |
| Cargo Only Maximum Qty / Pack | 60 L | | | | | | | | | | | | | | |
| Passenger and Cargo Packing Instructions | 353 | | | | | | | | | | | | | | |
| Passenger and Cargo Maximum Qty / Pack | 5 L | | | | | | | | | | | | | | |
| Passenger and Cargo Limited Quantity Packing Instructions | Y341 | | | | | | | | | | | | | | |
| Passenger and Cargo Limited Maximum Qty / Pack | 1 L | | | | | | | | | | | | | | |

Sea transport (IMDG-Code / GGVSee)

| | | |
|-------------------------------------|---------------------------------------|----------------|
| UN number | 1133 | |
| UN proper shipping name | ADHESIVES containing flammable liquid | |
| Transport hazard class(es) | IMDG Class | 3 |
| | IMDG Subrisk | Not Applicable |
| Packing group | II | |
| Environmental hazard | Marine Pollutant | |
| Special precautions for user | EMS Number | F-E , S-D |
| | Special provisions | Not Applicable |
| | Limited Quantities | 5 L |

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION**Safety, health and environmental regulations / legislation specific for the substance or mixture****TOLUENE(108-88-3) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

| | |
|--|---|
| Australia Exposure Standards | Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Part 2, Section Seven - Appendix I |
| Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals | Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5 |
| Australia Hazardous chemicals which may require Health Monitoring | Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6 |
| Australia Inventory of Chemical Substances (AICS) | Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 7 |
| Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2) | International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs |
| Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix F (Part 3) | |

METHYL ETHYL KETONE(78-93-3) IS FOUND ON THE FOLLOWING REGULATORY LISTS

| | |
|--|--|
| Australia Exposure Standards | Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2) |
| Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals | Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix F (Part 3) |
| Australia Inventory of Chemical Substances (AICS) | Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5 |

2-METHYLPENTANE(107-83-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS

| | |
|--|--|
| Australia Exposure Standards | Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2) |
| Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals | Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5 |
| Australia Inventory of Chemical Substances (AICS) | |

National Inventory Status

| National Inventory | Status |
|-------------------------------|--|
| Australia - AICS | Y |
| Canada - DSL | Y |
| Canada - NDSL | N (toluene; 2-methylpentane; methyl ethyl ketone) |
| China - IECSC | Y |
| Europe - EINEC / ELINCS / NLP | Y |
| Japan - ENCS | Y |
| Korea - KECI | Y |
| New Zealand - NZIoC | Y |
| Philippines - PICCS | Y |
| USA - TSCA | Y |
| Legend: | Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets) |

SECTION 16 OTHER INFORMATION

| | |
|----------------------|------------|
| Revision Date | 23/10/2018 |
| Initial Date | 23/10/2018 |

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other

Continued...

settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC—TWA: Permissible Concentration-Time Weighted Average
PC—STEL: Permissible Concentration-Short Term Exposure Limit
IARC: International Agency for Research on Cancer
ACGIH: American Conference of Governmental Industrial Hygienists
STEL: Short Term Exposure Limit
TEEL: Temporary Emergency Exposure Limit,
IDLH: Immediately Dangerous to Life or Health Concentrations
OSF: Odour Safety Factor
NOAEL :No Observed Adverse Effect Level
LOAEL: Lowest Observed Adverse Effect Level
TLV: Threshold Limit Value
LOD: Limit Of Detection
OTV: Odour Threshold Value
BCF: BioConcentration Factors
BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.