

## 6037 Outdoor Grass Carpet Adhesive

Roberts 6037 Outdoor Grass Carpet Adhesive is an all-weather solvent based (flammable) adhesive specifically formulated for the outdoor installation of non-stretch open weave polypropylene backed synthetic grass carpet. Not recommended for urethane and E.V.A backed carpets.

Roberts 6037 Outdoor Grass Carpet Adhesive develops high strength quickly and when cured will withstand unfavourable weather conditions. It will bond securely to cured concrete, asphalt, exterior grade wood and other clean paved surfaces and is ideal for use around swimming pools, balconies, outdoor recreational areas and other applications which are subject to moisture after fixing.

### Surface Preparation

To be in accordance with The Australian Standard 2455.1: 2007 "Textile Floor Covering Installation Practice". All surfaces to be bonded shall be dry, smooth, sound and clean. Subfloors must also be free of wax, grease and hydrostatic pressure. All concrete substrate floors should be tested for moisture content according to the above Australian Standard, prior to undertaking surface priming or installation of floorcovering.

### Application

Rough cut and lay out carpet according to manufacturer's instructions. Spread adhesive with the recommended notched trowel. Adhesive must be tacked up before floorcovering is lowered. Tack-up time will depend upon atmospheric conditions and can be determined by placing a small piece of floorcovering into the adhesive. When the floorcovering is pulled away, strings of adhesive should be apparent. If no tack or holding power has developed, wait five minutes re-checking installation according to floorcovering manufacturer's instructions. Do not allow heavy traffic for 24 hours. All seams must be sealed using Roberts 5216 Carpet Seam Adhesive. Do not use in rain or if rain is expected during or immediately after laying.

### Clean Up

To clean up equipment and adhesive spills, use Roberts 900 Cleaner/Thinner (Flammable). Roberts 900 is not recommended for removing adhesive from vinyl, carpet or painted surfaces.

### Typical Properties

<i>Appearance</i>	Brown
<i>Base</i>	Synthetic rubber
<i>Solids</i>	58% (approx)
<i>Viscosity</i>	Trowellable Mastic
<i>Shelf Life</i>	Up to 1 year in sealed container at 20°C
<i>Flash Point</i>	Less than 0°C
<i>Freezability</i>	Avoid freezing
<i>Packaging</i>	20, 4 litre

### Trowel Size

*Smooth backed carpet/Smooth substrate*  
2.4mm x 2.4mm x 2.4mm 'V' notched.  
Coverage up to 3.0m<sup>2</sup>/litre.

*Textured backed carpet/Rough substrate*  
3.2mm x 1.6mm x 3.2mm 'V' notched.  
Coverage up to 2.0m<sup>2</sup>/litre.

*Heavily ribbed carpet/Rough substrate*  
3.2mm x 3.2mm x 3.2mm 'U' notched.  
Coverage up to 1.6m<sup>2</sup>/litre.

### Contains

480ml/litre Liquid Hydrocarbons.

### Highly Flammable

Avoid contact with skin and eyes and avoid breathing vapour.

### First Aid

If poisoning occurs, contact a doctor or Poisons Information Centre.

If swallowed, **DO NOT** induce vomiting. Give a glass of water.

### Safety & Handling

Material Safety Data Sheet available upon request.

Issued: April 2007

The application, use and processing of our products is the responsibility of the user. Any technical or other advice, information or data provided by us, whether verbally, in writing or by way of trials or tests, is given without guarantee or warranty. Refer to Material Safety Data Sheets for information on Storage & Handling, Health and Safety, and Transport.

### RLA POLYMERS PTY LTD

ACN 004 709 915

215 Colchester Road, Kilsyth, Victoria 3137 Australia  
P.O. Box 147, Kilsyth, Victoria 3137 Australia  
Telephone: (03) 9728 1644 • Facsimile: (03) 9728 6009  
E-mail: info@rlapolymers.com.au • Web: www.rlapolymers.com.au

 A Vita Group Company



67 Dalgety Drive (P.O. Box 97-575)  
Manukau City, Auckland, New Zealand  
Telephone: (9) 268 0301  
Facsimile: (9) 268 0305