

R85 Fast Tack Carpet Adhesive

BENEFITS

- ✓ Installer Friendly
- ✓ Creating A Safer Work Environment
- ✓ Beneficial To Building Occupant
- ✓ Building Green Credits
- ✓ A Good Environmental Choice

FEATURES

- ✓ Green Star Compliant
- ✓ Solvent Free
- ✓ Very Low VOC Emission
- ✓ Anti-microbial Formulation
- ✓ Very Low Odour
- ✓ Australian Made

RLA GROUP GREEN SOLUTIONS PREMIUM COMMERCIAL PRODUCTS are helping you to have a safer work place. During the installation period and for some further time, they will help improve the occupied work space air quality by reducing greenhouse gas, solvent, organic and other volatile emissions.

PRODUCT DESCRIPTION

Roberts 85 Fast Grab Carpet Adhesive features solvent free, low odour, antimicrobial, low VOC water-based formulation to provide a tacky film of adhesive that is strong enough to eliminate any movement in the carpet after the installation is completed.

FOR BONDING

It is suitable for bonding Needle punch, Action Bac, Hessian back, tufted back and most woven back carpets in both double bond and direct stick installations. It can also be used to bond dual bond underlay to concrete and timber floor. The adhesive offers a quick grab and has excellent re-bonding for hard to hold carpets

SURFACE PREPARATION

To be in accordance with the Australian Standards 2455.1.2007 "Textile Floor Coverings Installation Practice".

All surfaces to be bonded to should be absorbent, dry, smooth, sound and clean. Subfloors should be free from wax, grease, paints, previously used adhesive, hydrostatic pressure, polishes, PVC base membranes, laitance (being the dusty unstable topping of poorly or insufficiently cured concrete) and any other impurities or contaminants that may affect adhesion.

The minimum subfloor temperature before commencing installation should be 10°C. It is recommended that all highly absorbent concrete floors are to be primed with R400 Floor & Wall Primer prior to the application of adhesive.

Test all concrete substrate flooring for moisture content, according to the current Australian Standards prior to priming or the installation of any floorcoverings.

Indentations and uneven concrete subfloors should be treated with the **Roberts** range of levelling compound and be in accordance with manufacturer's recommendations.

**adhesives hot melts tapes
levelling powders primers**

The application, use and processing of our products is the responsibility of the user. Any technical or other advice, information or data provided by us, whether verbally, in writing or by way of trials or tests, is given without guarantee or warranty. Refer to Material Safety Data Sheets for information on Storage & Handling, Health and Safety, and Transport.

RLA POLYMERS PTY LTD

ACN 004 709 915

215 Colchester Road, Kilsyth, Victoria 3137 Australia

P.O. Box 147, Kilsyth, Victoria 3137 Australia

Telephone: (03) 9728 1644 • Facs/mile: (03) 9728 6009

E-mail: info@rlapolymers.com.au • Web: www.rlagroup.com.au



SPREAD RATE & APPLICATION

Approximately 2-4 square metres per litre depending upon the size of the notched trowel used and absorbency of the substrate.

The notching recommended is 1.6mm (V1) for underlay to subfloor, 2.4mm (V2) for Hessian backed carpets and 3.2mm (V3) for Action Bac, Needle punch, woven or highly textured backings.

Allow adhesive to develop some initial tack – generally 5-10minutes at 20°C before lowering floorcovering into the wet film of adhesive and rolled to ensure transfer has occurred.

Tack-up times will depend upon atmospheric conditions and substrate absorbency.

In colder conditions, allow adhesive to remain open until tack and grab develop then lower in the carpet / underlay. Check to ensure that complete transfer of adhesive to the carpet / underlay has occurred and roll the finished installation with a 25-35kg roller.

Complete the installation according to floorcovering manufacturer's instructions.

Do not allow heavy traffic for 24 hours.

Note: RLA Group Pty Ltd strongly recommends the use of the Roberts range of carpet seaming tape on all dual bond carpet installations.

CLEAN UP

Clean tools immediately after use with warm soapy water.

Do not thin adhesive.

TYPICAL PROPERTIES

Appearance: Off white

Base: Latex

Viscosity: Trowellable

Solids: 76% Solids

Initial Tack: 5-10minutes at 20°C

CONTAINER SIZE

15 litre plastic pails

STORAGE

Keep in well ventilated areas stored out of direct sunlight.

SHELF LIFE

12 months in unopened containers stored out of direct sunlight.

SAFETY & HANDLING

A Safety Data Sheet is available upon request.

**adhesives hot melts tapes
levelling powders primers**

The application, use and processing of our products is the responsibility of the user. Any technical or other advice, information or data provided by us, whether verbally, in writing or by way of trials or tests, is given without guarantee or warranty. Refer to Material Safety Data Sheets for information on Storage & Handling, Health and Safety, and Transport.

RLA POLYMERS PTY LTD

ACN 004 709 915

215 Colchester Road, Kilsyth, Victoria 3137 Australia

P.O. Box 147, Kilsyth, Victoria 3137 Australia

Telephone: (03) 9728 1644 • Facs/mile: (03) 9728 6009

E-mail: info@rlapolymers.com.au • Web: www.rlagroup.com.au





Warranty Statement

RLA Polymers guarantees this product against manufacturing defects and guarantees it to be manufactured to our published specification.

We certify that when fully cured this product is suitable for use and will perform as described in our technical data sheet or other published materials.

RLA Polymers will replace product free of charge when purchased from any legally verifiable source, and where product is proven to have been stored, handled and installed according to instructions published on our packaging and within the stated shelf life. The Installation of all materials must be carried out in accordance with the relevant Australian Standard and the Floorcovering Manufacturers instructions and the floorcoverings must have been subject to normal traffic conditions.

Warranty doesn't not apply if damage, loss, failure to follow instructions or other circumstances are out of our control.

Sufficient time and access to investigate any complaint must be accorded to RLA Polymers.

The consumer is responsible for any expenses incurred in making a claim.

A claim form can be requested by:

Phone: 1800 242 931

Email: info@rlapolymers.com.au

Mail: 215 Colchester Road Kilsyth Victoria 3137 (attn Customer Services)

Australian Consumer Law

Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage.

You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.

The benefits under our warranty are in addition to other rights and remedies available to the consumer under the law in relation to the goods and services to which the warranty relates.

Disclaimer

All Statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed.

Users assume all risk and liability resulting from the use of the product and must confirm the suitability thereof by their own tests.

Conditions of Sale contain a limited warranty against manufacturing defects.

Issued: June 2016

The application, use and processing of our products is the responsibility of the user. Any technical or other advice, information or data provided by us, whether verbally, in writing or by way of trials or tests, is given without guarantee or warranty. Refer to Material Safety Data Sheets for information on Storage & Handling, Health and Safety, and Transport.

RLA POLYMERS PTY LTD

ACN 004 709 915

215 Colchester Road, Kilsyth, Victoria 3137 Australia

P.O. Box 147, Kilsyth, Victoria 3137 Australia

Telephone: (03) 9728 1644 • Facs/mile: (03) 9728 6009

E-mail: info@rlapolymers.com.au • Web: www.rlagroup.com.au



adhesives hot melts tapes
levelling powders primers

